

workcentre
PRO 580**XEROX WORKCENTRE® PRO 580
MULTIFUNCTION FAX SOLUTION****Key features at a glance:****Faxing**

- 33.6 Kbps modem speed
- Many convenience features, including one-touch, speed and group dialing, handset included

Direct Connect Printing


- 600 dpi
- Envelopes

Local Scanning

- High quality monochrome scanning
- TextBridge® Pro Millennium OCR software

Convenience Copying

- Digital copying from the 20-page ADF
- 8 copies a minute



THE DOCUMENT COMPANY

XEROX

XEROX WORKCENTRE PRO 580 MULTIFUNCTION FAX SOLUTION

The affordable multifunction fax solution...

Whether you work in a small business, a home office, or an executive suite, it takes the right tools to be competitive. Compact and economical, the WorkCentre Pro 580 multifunction fax solution combines quality faxing, with direct connect printing, OCR scanning and convenience copying. One solution to meet all your communication needs.



workcentre
PRO 580

SPECIFICATIONS

Plain Paper Fax

Compatibility	ITU T.30
Modem Speed	33.6 Kbps
Transmission	3 seconds per page
Fast Scan	3 seconds per page
Compression	MMR/MR/MH with ECM
Resolution	Standard (200 x 100 dpi) Fine (200 x 200 dpi) Super Fine (300 x 300 dpi)
Halftones	64 Level error diffusion
Memory	2 MB 160 pages
Battery Backup	30 minutes
One Touch	20 locations
Speed Dial	80 locations
Group Dial	Up to 20 groups
Handset	Included
Convenience	100 location broadcast, memory transmission, Delay TX, Memory RX, Voice Request, TTI, RTI, Polling, Flash, Auto reduction, Chain Dialing, ANS/FAX mode, Distinctive Ring Detection, Priority Transmission, Receive Footer

Printer

Technology	Laser Monochrome
Speed	8 pages per minute
Memory	4 MB
Resolution	600 x 600 dpi
PDL	GDI
Effective Print Width	8.2" (208 mm)
Toner Save Mode	Yes

Scanner

Resolution	300 x 300 dpi Up to 4800 dpi interpolated, pre-scan 75 dpi
Halftones	8 bit
Effective Scan Width	8.2" (208 mm)
Scan Length	Up to 1000 mm
Scan Driver	TWAIN
Speed	25 seconds per page

Copier

Speed	8 copies per minute
Resolution	Scan: 300 x 300 dpi, Print: 600 x 600 dpi
Halftones	64 levels
Reduce/Enlarge	50% to 200% 1% increments
Multiple Copies	Up to 99

Media Handling

Automatic Document Feeder	20 sheets
Minimum Size	5.8" x 5.0" (148 x 128 mm)
Maximum Size	8.5" x 14" (216 x 356mm)
Media Weight	12.5 – 28 lbs (47 – 105 g/m ²)
Paper Weight	
Main Tray	16 – 24 lbs (60 – 90 g/m ²)
Bypass Tray	16 - 43 lbs (60 – 161 g/m ²)
Input Paper Capacity	
Main Tray	150 sheets
Bypass Tray	Single sheet
Output Capacity	100 sheets
Media Types	Plain paper, transparencies, envelopes, card stock

Supplies

Approximate Yield	
Laser Printer Cartridge	2,500 pages @ 5% coverage

Software Included

OCR	TextBridge® Pro Millennium
Device Management	ControlCentre Lite

General

Power	110/127 VAC 50/60 Hz
Current	2.5 Amps
Power Consumption	Min 9.5W/Max 130W ENERGY STAR® compliant

Dimensions

	14.5"W x 14"D x 7.7"H (370 mm W x 356 mm D x 195 mm H)
--	--

Weight

	17 lbs. (7.7kg)
--	-----------------

Operating Environment

Temperature	50° – 89.6° F (10° – 32° C)
Humidity	20 – 80%

System Specifications

Minimum Requirements	133 MHz Pentium, 32 MB Memory, 120 MB free disk space, CD ROM Drive
Operating System	Microsoft Windows 95/98/ME/ NT4.0/2000
Interface	IEEE 1284 Bi-directional Parallel

THE DOCUMENT COMPANY

XEROX



Configuration availability may vary by location.

© 2001 Xerox Corporation. All rights reserved. Xerox, The Document Company, WorkCentre and the digital X are registered trademarks of XEROX CORPORATION. In support of Xerox's environmental leadership goals, the Xerox WorkCentre Pro 580 may contain some recycled components that are reconditioned. Windows and Windows NT are registered trademarks of Microsoft Corp. PaperPort and TextBridge are registered trademarks of ScanSoft, Inc. ENERGY STAR is a registered trademark of the Environmental Protection Agency. Xerox Corporation reserves the right at any time to change the specifications of the equipment described herein without notice. 10/01 610P710190

Available at: