

Recommended Xerox Materials for DocuColor 5760/5765

For use in USA and Canada

Revision 2.3, Publish Date: Sept. 27th, 2002

Last Revision 2.2 was published on July 3rd, 2002

For the most recent version of this quarterly published document, visit www.xdss.com, select "Free Downloads", then "Color".

Important Note:

Media recommendations made in this publication are based on qualification tests* conducted using standard test images with moderate to heavy image area coverage. Test duration for each product/media type is based on the suggested machine monthly copy/print volume. Test machines are maintained within specifications defined by user documentation.

* Testing Environment temperature range of 60-75 deg. F, Relative Humidity range 20-40%.

Machine reliability specifications may be affected by increased usage of Thick Paper mode. In addition, variances in machine reliability may occur due to extended use of some media types. Your Xerox Sales or Service representative can advise you on using Thick Paper mode or special application media types for long duration copy/print runs.

For specifications and a description of the various media types discussed in this publication, please refer to the Color Material Usage Guide (reorder number 701P34322) that comes with your equipment.

© 2001 Xerox Corporation. All rights reserved.

Xerox®, The Document Company®, the stylized X®, and all Xerox product names and product names and product numbers mentioned in this publication are trademarks of Xerox Corporation. Other company trademarks are also acknowledged.

Xerox Recommended Material List (US and Canada)

For the most recent version of this document, visit www.xdss.com/ select "Free Downloads", then "Color".

Internal Trays: Normal (Plain Paper) Mode (64-105 gsm)

Bypass Tray: Normal Mode (64-105gsm) , Heavyweight (Thick) Mode (106-163gsm) Transparency

DC5760/ 5765

**M=Manual Duplex S=Simplex
PCW=Post Consumer Waste**

| Media | Mode | Weight | Re-Order # | Type | Size | Internal | Bypass | Additional Information |
|--|------------------|---------------|------------------|---------|----------|----------|--------|------------------------|
| Xerox Digital Color Xpressions + | Normal Mode | 90 gsm / 24lb | 3R11380 | | 8.5 x 11 | S | M | |
| | | | 3R11381 (3 Hole) | | 8.5 x 11 | S | M | |
| | | | 3R11382 | | 8.5 x 14 | S | M | |
| | | | 3R11383 | | 17 x 11 | S | M | |
| | Heavyweight Mode | 105gsm/ 28lb | 3R11385 | | 8.5 x 11 | S | M | |
| | | | 3R11386 | | 17 x 11 | S | M | |
| | | | 3R11387 | | 8.5 x 11 | | M | |
| | | | 3R11390 | | 8.5 x 11 | | M | |
| Heavyweight Mode | 163gsm/ 60lb | 3R11391 | | 17 x 11 | | M | | |
| | | | | | | | | |
| Xerox Digital Color Xpressions 98' (Ultra White) | Normal Mode | 105gsm/ 28lb | 3R5529 | | 8.5 x 11 | S | M | PCW=20% |
| | | | 3R5530 | | 17 x 11 | S | M | |
| | Heavyweight Mode | 163gsm/ 60lb | 3R6385 | | 8.5 x 11 | | S | PCW=20% |
| | | | 3R6386 | | 17 x 11 | | S | |
| Xerox Digital Color Graphics | Normal Mode | 105gsm/ 28lb | 3R11164 | Cream | 8.5 x 11 | S | M | PCW=30% |
| | | | 3R11168 | White | 17 x 11 | S | M | |
| | | | 3R11165 | Warm | 8.5 x 11 | S | M | |
| | | | 3R11169 | White | 17 x 11 | S | M | |
| | | | 3R11166 | White | 8.5 x 11 | S | M | |
| | | | 3R11170 | Fiber | 17 x 11 | S | M | |
| | | | 3R11167 | Cream | 8.5 x 11 | S | M | |
| | | | 3R11171 | Fiber | 17 x 11 | S | M | |

Xerox Recommended Material List (US and Canada)

For the most recent version of this document, visit www.xdss.com/ select "Free Downloads", then "Color".

Internal Trays: Normal (Plain Paper) Mode (64-105 gsm)
 Bypass Tray: Normal Mode (64-105gsm) , Heavyweight
 (Thick) Mode (106-163gsm) Transparency

DC5760/ 5765

**M=Manual Duplex S=Simplex
 PCW=Post Consumer Waste**

| Media | Mode | Weight | Re-Order # | Type | Size | Internal | Bypass | Additional Information |
|--|-------------------|---------------|------------|-------|----------|----------|--------|-------------------------------------|
| Xerox Digital Color Super Gloss | Heavyweight Mode | 8pt./160gsm | 3R6290 | | 8.5 X 11 | | S | Copier Only. |
| Xerox Digital Color Trifold Brochures | Heavyweight Mode | 120gsm / 32lb | 3R12310 | | 8.5 X 11 | | M | Short Edge Feed in the Bypass Tray. |
| Xerox One- Step Transfer Paper | Heavyweight Mode | | 3R5811 | | 8.5 X 11 | | S | Black & White Only. |
| | | | 3R5812 | | 11 X 17 | | S | |
| Xerox Digital Color Xpressions Gloss Coated Labels | Heavyweight Mode | | 3R5770 | 1- up | 8.5 X 11 | | S | |
| | | | 3R5771 | 4-up | 8.5 X 11 | | S | |
| Xerox Digital Color Xpressions Matte Coated Labels | Heavyweight Mode | | 3R5772 | 1- up | 8.5 X 11 | | S | PCW=10% |
| | | | 3R5773 | 4-up | 8.5 X 11 | | S | |
| Xerox Bright White Labels | Heavyweight Mode | | 3R12177 | 1- up | 8.5 X 11 | | S | PCW=20% |
| | | | 3R12179 | 30-up | 8.5 X 11 | | S | |
| Xerox High Speed Labels | Heavyweight Mode | | 3R4476 | 1- up | 8.5 X 11 | | S | |
| | | | 3R4475 | 8-up | 8.5 X 11 | | S | |
| | | | 3R5719 | 14-up | 8.5 X 11 | | S | |
| | | | 3R4474 | 24-up | 8.5 X 11 | | S | |
| | | | 3R3139 | 33-up | 8.5 X 11 | | S | |
| Xerox Digital Color Transparency | Transparency Mode | | 3R5765 | | 8.5 x 11 | | S | PCW=30% minimum |
| Xerox Removable Stripe Transparency | Transparency Mode | | 3R3108 | | 8.5 x 11 | | S | PCW=25% |